
# Visual Cortex on a Chip

Large-scale, real-time functional models of mammalian visual cortex on a GPGPU



## Steven P. Brumby (brumby@lanl.gov),

Amy E. Galbraith, Michael Ham, Garrett Kenyon, and John S. George Los Alamos National Laboratory, Los Alamos, New Mexico, USA GPU Technology Conference 2010, San Jose CA




http://synthetic-cognition.lanl.gov



# Large-scale, real-time functional models of mammalian visual cortex on a GPGPU

### Concept



Full-scale simulation of human vision is a petascale computing challenge, and is now feasible with Roadrunner.



### **Project Goals**

Science Goal: Explore new neuroscience-inspired artificial neural networks using unique petascale computing resources at LANL (Roadrunner) for robust, human-like feature and object extraction from video and imagery datasets


Performance Goal: Full-scale, real-time model of human visual cortex ~ 1080p HD video at >10 fps.

#### **Technical Approach**

- Full-scale model of visual cortex using: synaptic plasticity / machine learning, models of color processing, feed-back/lateral connectivity, and spiking dynamical neurons.
- 2. Unique petaflop (Roadrunner/Cell) and multi-teraflop single-rack GPGPU-accelerated high performance computing systems.
- 3. A \$6M R&D investment by DOE/LANL LDRD-DR, NSF, and DARPA.


http://synthetic-cognition.lanl.gov





Computing hardware for large-scale simulations of human cortex exists now: With petascale supercomputers, such as LANL's Roadrunner, large-scale simulations can be run at real-time on full-scale visual datasets (~months of HD video). GPGPU enables experiments at small-mammal scale using machines costing a few k\$.





• Mouse cortex: 4,000,000 neurons

• Cat cortex: 300,000,000 neurons

• Monkey cortex: 6,000,000,000 neurons

• Human cortex: 11,000,000,000 neurons (~100G neurons whole brain)

■~10,000 synapses (connections) per neuron

■ 130 types of neurons in human brain





Existing Models
Grossberg/Carpenter ART
Poggio MIT models
LeCun Deep networks







Biochemical Models
Blue Brain (EPFL)

# Feedback Loops



## **Synaptic Plasticity**








 $\Delta W_{ii}$ 


 $\Delta W_{ii}$ 

**Next generation Artificial Neural Networks:** Goal is functional models of visual cortex based on recent work in neuroscience.










E.M. Izhikevich & G.M. Edelman, (2008) Proc. National Acad. Sci. 105:3593-3598 Large-Scale Model of Mammalian Thalamocortical Systems,
















## **Processing in Retina**

Local contrast equalization, for each patch set mean to zero and local Euclidean norm to 1.









## **Processing in S-cells**

Radial Basis Functions with standard oriented Gabor neuron weight vectors [3-5].

$$s_{\text{RBF}}(\boldsymbol{r}, \boldsymbol{w}_G) = \exp\left(-\frac{1}{2}\beta(\boldsymbol{r} - \boldsymbol{w}_G)^2\right)$$

$$w_G = w(\theta, \gamma, \sigma, \lambda, \phi) = \exp\left(-\frac{1}{2\sigma}\left(x_\theta^2 + \gamma y_\theta^2\right)\right)\cos\left(\frac{2\pi x_\theta}{\lambda} + \phi\right)$$

### **Processing in C-cells**


MAX Function over S-cell receptive fields.

$$c_{\text{MAX}}(\mathbf{s}) = \max_{i \in I_j} (\{s_i\})$$

#### Standard model of visual cortex


LANL's PANN code is a high performance implementation in C++/C and Python of a Neocognitron model [Fukushima; Poggio et al.].





LANL supercomputing assets have allowed us to reach full-scale processing at real-time video rates. Codes can also run on GPU or conventional multi-core machines.





LANL codes exploit conventional multi-core/ multi-cpu clusters, vector processing on cpu cores (SSE), and "cluster on a chip" hardware (CELL, GPGPU).







Fig. 5. Accuracy for supervised binary-classification of animal versus no animal images as a function of training set size for V1-V2 model using imprinting (red dashed line) or Hebbian learning (blue solid line). Lines show fit of a simple model,  $A = a + b \ln(N_T)$ , with 1 standard deviation error bars.

Brumby et al., IEEE Proc. AIPR 2009.







Hebb–Oha learning rule:  $\Delta w = \lambda y(r,w)(r-w)$ Visual cortex models are self-organizing using neuroscience-inspired learning rules.


















#### **Vehicle Tracking in UAV-like Video**

We have preliminary results using a learned model of primary visual cortex on public-release UAV-like imagery of vehicle detection and tracking scenarios provided by the DARPA/DSO Neovision2 program. We are currently working to explore and optimize the object-recognition capabilities of visual cortex models under different conditions of learning rule, initial network topology, and training set size. Initial results suggest that visual cortex models such as PANN are a promising approach to this hard visual pattern recognition problem. GPGPU acceleration may be the key enabling technology for this type of application, as exploiting the GPGPU enables a better than order-of-magnitude speed-up of execution of the model on workstations, enabling learning of better models and faster execution of the final model.










# Large-scale, real-time functional models of mammalian visual cortex on a GPGPU

### Concept



Full-scale simulation of human vision is a petascale computing challenge, and is now feasible with Roadrunner.



### **Project Goals**

Science Goal: Explore new neuroscience-inspired artificial neural networks using unique petascale computing resources at LANL (Roadrunner) for robust, human-like feature and object extraction from video and imagery datasets

Performance Goal: Full-scale, real-time model of human visual cortex ~ 1080p HD video at >10 fps.

#### **Technical Approach**

- Full-scale model of visual cortex using: synaptic plasticity / machine learning, models of color processing, feed-back/lateral connectivity, and spiking dynamical neurons.
- 2. Unique petaflop (Roadrunner/Cell) and multi-teraflop single-rack GPGPU-accelerated high performance computing systems.
- 3. A \$6M R&D investment by DOE/LANL LDRD-DR, NSF, and DARPA.

http://synthetic-cognition.lanl.gov

